

Pack-Master Air Compactor

offered by **S&G Enterprises, Inc**



- Reduce your disposal and storage costs.
- Simply place a drum of material on the base, lift arm and compact it by operating the joy stick on the arm.
- Two-handed safety lever keeps the operator out of harms way.
- Add optional wheel kit to easily move the PackMaster from department to department.
- Compaction cycle is just 30 seconds with 100 psi air supply.
- Spark resistant model also available. Ask for part # 10001453.
- 18 month limited warranty

SPECIFICATIONS

PackMaster Air

Part #10001259

DIMENSIONS:	76"h x 36"w x 27"d	Required Operating Clearance: 80"h x 38"w x 48"d
SHIPPING:	220 lbs on pallet via common carrier (F.O.B. Aurora Colorado 80011)	
DRUM CLEARANCE:	Height: 39"	Width: 25.75"
PRESSURE PLATE:	55 gallon: 20" diameter (standard)	30 gallon: 17" diameter (optional)
AIR CYLINDER:	Commercial grade, 6" diameter x 24" stroke length with oversized 1.75" piston rod	
AIR REQUIREMENTS:	Standard shop air (8 cfm @ 100 psi) Maximum 150 psi	
COMPACTION FORCE:	2600 lbs of force @ 100 psi	3900 lbs of force @ 150 psi
CONSTRUCTION:	All welded structural steel and industrial grade components.	
SAFE:	Two-handed safety lever operation keeps hands and face away from barrel. When air is disconnected, pressure plate cannot fall.	
EASY TO USE:	Place drum of material on the base, lift safety lever, compact or retract with joystick control. Drop safety lever to secure pressure plate after retraction.	
WARRANTY:	Covered by Newstripe's 18 month limited warranty.	
ACCESSORIES:	Listed on reverse side.	
CAUTION:	Unit is not designed for crushing of glass containers or items that may shatter or contain volatile vapors.	

Visit our website at www.RamFlat.com or call toll free 1-888-RAM-FLAT

